



501 & 505 WS



511 & 515 WS

- 2 year warranty
- Full LCD display and user interface giving uncomplicated machine status updates
- Designed for the most demanding environments
- Breaktank as standard
- Double skinned minimising both acoustic output and reduced heat loss
- 505 WS with internal continuous water softener
- Low water consumption
- Three standard cycle options
- Extensive range of special cycle options
- GLASS cycle automatically changes parameters to suit glass washing
- SANITISING cycle balances wash time and temperatures to achieve a standard rating of AO 30
- LONG cycle for intensive wash or for glass renovation
- GREEN cycle for economy, reduces water consumption and operates with lower temperatures
- ACT extremely intensive cycle for the dirtiest products by running two complete cycles
- Detergent and rinse aid delivery by precise peristaltic pumps
- Priming and dosing of chemicals enabled from fascia controls
- Comprehensive automatic self-cleaning cycle
- Drain pump as standard
- Surface scrap trays as standard
- Hi-level information retrieval to aid both installation and service technicians
- 501 & 505 WS Supplied with two open cup/glass racks
- 511 & 515 WS supplied with one open, one pegged plate rack & cutlery basket

## Technical

- Standard voltage 240V – single phase
- All models can be supplied for 3 phase
- Suitable for hot (max 50°C) or cold\* water supply at 2 to 4 bar dynamic supply pressure
- Wash temperature 60°C (adjustable)
- Rinse temperature Evolution 501 & 505 WS 65°C (adjustable), 78°C when Plates cycle selected
- Rinse temperature Evolution 511 & 515 WS 78°C (adjustable)
- Cycle times between 90 & 715 secs, including special cycles

Drain pump versions require a waste up-stand for correct operation.

Restrictive waste connections should be avoided for all installations.

\*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.



| Model            | Rack size mm | Useable Height mm | Dimensions mm W x D x H | Standard Cycle Options | Power kW    | Amps Required | Price  |
|------------------|--------------|-------------------|-------------------------|------------------------|-------------|---------------|--------|
| Evolution 501    | 500          | 250               | 600 x 605 x 715#        | 3 Cycles               | 2.6/4.5/6.5 | 13/20/30##    | £3,750 |
| Evolution 505 WS | 500          | 250               | 600 x 605 x 715#        | 3 Cycles               | 2.6/4.5/6.5 | 13/20/30##    | £4,180 |
| Evolution 511    | 500          | 345               | 600 x 605 x 815#        | 3 Cycles               | 2.6/4.5/6.5 | 13/20/30##    | £3,960 |
| Evolution 515 WS | 500          | 345               | 600 x 605 x 815#        | 3 Cycles               | 2.6/4.5/6.5 | 13/20/30##    | £4,650 |

# Height excludes adjustable feet which will add 10 to 20mm.

## Machines will be supplied for 30 amp supply as standard, if 13 or 20 amp ordered they will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

It is strongly recommended that 500mm machines are installed on hot water fill (max 50°C) for optimum performance.